




## PERFETTO IN-GROUND 3W 3000K CRI80 WITH NOT REPLACEABLE LENS

Design: Studio Tecnico Ivela



Product code	Color
1453000	Stainless steel

### General Specifications

Product type	: Outdoor recessed
Mounting type	: Ceiling - recessed, Ground - recessed, Wall - recessed
Description	: Recessed ground walk-over light for both indoor and outdoor, equipped with latest generation LEDs and with not replaceable lens. It can be installed on the floor, on the wall or on the ceiling with the special springs. Recessed housing and springs for installation in-ground (to be ordered separately). 700mA driver, should be ordered separately. Professional optic devices for better visual comfort are available.
Notes	: Max 3 fittings can be connected to the driver 81-02531.
Indoor/outdoor lights	: Indoor, Outdoor
Applications	: Gardens, Residential, Walkways

### Lighting specifications

Lamp description	: LED 350lm 3W 3000K CRI80
Nominal lumens on thermal regime	: 350
Efficiency L.O.R. (%)	: 90
Delivered lumens (lm)	: 315
Lamp wattage (W)	: 3
Color temperature (K)	: 3000
Average lamp life (h)	: L80B10 50.000
Photobiological risk group	: RG1

### Physical Specifications

Body	: Body and frame in brushed stainless steel
Closing Screen	: Tempered and bevelled safety glass (8mm)
Gaskets	: Silicone
Mechanical load (Kg)	: 500

### Electrical Specifications


Cable gland	: Nickel-plated brass cable gland M12x1, 5
Driver current (mA)	: 700
Supply cable	: H05RN-F 2x1 mm <sup>2</sup> , 2 mt. length

### Weight and Dimensions

Shape	: Round
External diameter (mm)	: 58
Length (mm)	: 60
Recessed depth (mm)	: 77
Weight (Kg)	: 0.7

### Optical Specifications


Aiming	: Fixed
Light distribution	: Symmetric
Light emission	: Direct
Light beam	: 10°



## ACCESSORIES



Product Code : 84108  
Name : IP 68 rated cable connector




Product Code : 160821  
Name : 10mt Supply cable coil, H05RN-F 2x1 mm²



Product Code : 28-4200-30  
Name : Honeycomb  
Finish : Black painted  
Shape : Round




Product Code : 28-4177-47  
Name : Prismatic spread lens  
Shape : Round



Product Code : 28-4195-30  
Name : Recessed housing for installation in-ground  
Shape : Round  
Notes : Recessed housing to be ordered separately




Product Code : 28-4197-48  
Name : Springs for false ceiling and paneling mounting min.1mm max15mm.




Product Code : 28-4177-4730  
Name : Black silk-screened clear glass, with an anti-dazzling and an asymmetric effect  
Shape : Round

## Drivers



Product Code : 81-02531  
Name : Driver 700mA Constant current (max.12W)  
description : Max 3 fittings can be connected to the driver.

**PERFETTO IN-GROUND 3W 3000K CRI80 WITH NOT REPLACEABLE LENS**
*Design: Studio Tecnico Ivela*

Lamps	Lamp categories	Lamp wattage (W)	Nominal lumens on thermal regime (lm)	Color temperature (K)	Color rendering (CRI)
	LED	3	350	3000	80