



LED

Norms: EN 60598-1, EN 60598-2-1



IP 40

24V DC

850°C

PRODUCT DESCRIPTION

Areas of Application: Commercial, Business areas, Housing, Art and Culture spaces. Offices, Public buildings, Hotel and Restaurant services.

Mounting: Suspended.

Light Distribution: Direct / Indirect.

Light Source: LED 4000K, CRI>90, 60.000h life (@L80, B10, Ta 25 °C).

Optical System: Diffuser: Opal polycarbonate.

Control Gear: Not included.

Materials: Body: Extruded aluminium.

Surface Finish: Powder coated.

bLINE - Opal polycarbonate diffuser



LED	UGR	W	Lm	V	η(%)	AxB(mm)	kg	ORDER CODE
	≤22	28	2600	24	46	Ø650x35	2	90400.L650.0
	≤19	42	3900	24	50	Ø970x35	3	90400.L970.0
	≤19	54	5070	24	51	Ø1255x35	4	90400.L125.0
	≤19	67	6240	24	55	Ø1540x35	5	90400.L154.0
	-	85	7930	24	-	Ø1955x35	6	90400.L195.0

Note:
To complete the product add ceiling rose. Please order separately. Suspension kit is included in the product (1,5 m).
In the option RGBW, the product mandatorily includes the transparent current supply cable.

Example code for order: 90400.L195.0 (ORDER CODE) + W(COLOUR/FINISH) + 2000 + 9752(OPTIONS)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.


COLOUR / FINISH		DIMENSIONS	
Code	Description		
W	White		Trimless ceiling rose
G	Grey		50 Ø120 Ø128
B	Black		Recessed ceiling rose
U	Blue		82 Ø150 Ø128
V	Green		Surface ceiling rose
T	Yellow		41,5 Ø400
K	Red		
N	Jungle		
D	Golden eye		
O	Sahara		
L	Autumn		
R	Rusty chain		
C	Pure chocolate		
1	Mist		
9	Dark rock		
I	Carbon		

OPTIONS


Colour temperature		Surface ceiling rose	
	2700K	HF	Order code 9752
	Tunable White (3000K - 5700K)	DALI	9753
	RGB White (2700K)	OmniaControl (Voice/App)	9754
	• TW and RGBW are only available with OmniaControl.	• To complete this option, please add ceiling rose colour.	
Recessed ceiling rose		Trimless ceiling rose	
	HF	HF	Order code 9758
	DALI	DALI	9759
	OmniaControl (Voice/App)	OmniaControl (Voice/App)	9760
	• To complete this option, please add ceiling rose colour.	• To complete this option, please add ceiling rose colour.	

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.


PHOTOMETRY




OREO In Ø650mm
bLINE 4000K



OREO In Ø970mm
bLINE 4000K



OREO In Ø1255mm
bLINE 4000K



OREO In Ø1540mm
bLINE 4000K

TO SPECIFY:
Circular LED luminaire, for horizontal suspension. Extruded aluminium body with 35x35mm, epoxy polyester powder-coated. Available in 5 sizes (Ø650, 970, 1255, 1540 and 1955mm), with bLINE diffuser, opal polycarbonate clip-in diffuser. With inward light. Standard version in 4000K LED, CRI>90, 60.000h lifetime (@L80, B10, Ta 25 C) and without any visible power-supply cable. Ceiling rose available as recessed mounted with trim or trimless or surface mounted, in on/off, dimmable DALI or OmniaControl. 2700K, Tunable White and RGB White available as options. Available in 16 different colours. – as Roxo Lighting OREO IN.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.